154- $130.00

Patent

Attorney's Docket No. 032287-001

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of	)	
	)	
Johann PFEIFFER	)	
	)	Group Art Unit: Unassigned
Application No.: 08/981,519	)	
	)	Examiner: Unassigned
Filed: December 29, 1997	)	
	)	
For: METHOD OF BI-DIRECTIONAL DATA TRANSMISSION OVER A TWO-WIRE LINE	)	

TRANSMITTAL LETTER FOR MISSING PARTS OF APPLICATION

BOX: MISSING PART
Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

In complete response to the Notice to File Missing Parts of Application Under 37 C.F.R. § 1.53(e) dated February 17, 1998, enclosed please find:

[x] a Combined Declaration and Power of Attorney signed by the inventor(s) and the surcharge of [ ] $65.00 [x] $130.00 as set forth in 37 C.F.R. § 1.16(e);

[ ] Note that the inventor(s) identified on the currently filed Combined Declaration and Power of Attorney are different than listed on the application filing papers.

[ ] a Declaration Claiming Small Entity Status, and a Request for Refund;

[ ] a Petition for Extension of Time;

[ ] a verified English translation of the Application, and the $130.00 fee as set forth in 37 C.F.R. § 1.17(k);

[x] an Assignment document and the $40.00 Assignment Recording Fee;

03/23/1998 UWALKER 00000024 08981519
01 FC:154

[ ] other 130.00 OP;

[x] a check in the amount of $ 170.00 for the fee due; and

[ ] charge $_____ to Deposit Account No.02-4800 for the fee due.

The Commissioner is hereby authorized to charge any appropriate fees under 37 C.F.R. §§ 1.16, 1.17 and 1.21 that may be required by this paper, and to credit any overpayment, to Deposit Account No. 02-4800. This paper is submitted in triplicate.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

P.O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620

By: _____
Kris V. Kalidindi
Registration No. 41,461

Date: March 17, 1998

Rec'd PCT/PTO 29 DEC 1997

FORM-PTO-1390 (Rev. 10-96) U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371

ATTORNEY'S DOCKET NUMBER: 032287-001

U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5): 08/981519 Unassigned

INTERNATIONAL APPLICATION NO.	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED
PCT/AT96/00112	21 June 1996	26 June 1995

TITLE OF INVENTION
METHOD OF BI-DIRECTIONAL DATA TRANSMISSION OVER A TWO-WIRE LINE

APPLICANT(S) FOR DO/EO/US
Johann PFEIFFER

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and the PCT Articles 22 and 39(1).
4. ☒ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
   a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
   b. ☒ has been transmitted by the International Bureau.
   c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US)
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
   a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
   b. ☐ have been transmitted by the International Bureau.
   c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
   d. ☒ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern other document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A FIRST preliminary amendment.
    ☐ A SECOND or SUBSEQUENT preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☒ Other items or information:

Request for Preliminary Examination; English Translation thereof; Preliminary Examination Report; and Information Sheet

U.S. APPLICATION NO (If known, see 37 C.F.R 1 50)	INTERNATIONAL APPLICATION NO	ATTORNEY'S DOCKET NUMBER
Unassigned	PCT/AT96/00112	032287-001

17. ☒ The following fees are submitted:	CALCULATIONS	PTO USE ONLY
Basic National Fee (37 CFR 1.492(a)(1)-(5)):		
Search Report has been prepared by the EPO or JPO $930		
International preliminary examination fee paid to USPTO (37 CFR 1.482) $720.00		
No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) $790.00		
Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO $1070.00		
International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) $98.00		
ENTER APPROPRIATE BASIC FEE AMOUNT =	$ 930.00	
Surcharge of **$130.00** for furnishing the oath or declaration later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(e)).	$ ---	

Claims	Number Filed	Number Extra	Rate		
Total Claims	7 -20 =	0	X$22.00	$ - 0 -	
Independent Claims	1 -3 =	0	X$82.00	$ - 0 -	
Multiple dependent claim(s) (if applicable)			+$270.00	$ ---	
TOTAL OF ABOVE CALCULATIONS =				$ 930.00	
Reduction for 1/2 for filing by small entity, if applicable. Verified Small Entity statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).				$ ---	
SUBTOTAL =				$ 930.00	
Processing fee of **$130.00** for furnishing the English translation later than ☐ 20 ☐ 30 months from the earliest claimed priority date (37 CFR 1.492(f)). +				$ ---	
TOTAL NATIONAL FEE =				$ 930.00	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). $40.00 per property +				$ ---	
TOTAL FEES ENCLOSED =				$ 930.00	
				Amount to be: refunded	$
				charged	$

a. ☒ A check in the amount of $ 930.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. 02-4800 in the amount of $_____ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 02-4800. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Ronald L. Grudziecki
BURNS, DOANE, SWECKER & MATHIS, L.L.P.
P.O. Box 1404
Alexandria, Virginia 22313-1404

SIGNATURE

Steven M. du Bois
NAME

35,023
REGISTRATION NUMBER

D

PCT WORLD ORGANISATION FOR INTELLECTUAL PROPERTY
International Office
INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International patent classification[6] : H04L 5/14 — A1

(11) International publication number: WO 97/01900

(43) International publication date: 16 January 1997 (16.01.97)

(21) International application number: PCT/AT96/00112

(22) International filing date: 21 June 1996 (21.06.96)

(30) Data relating to the priority:
A 1087/95 26 June 1995 (26.06.95) AT

(71)Applicant (for all designated States except US): ERICSSON AUSTRIA AG [AT/AT]; Pottendorfer Strasse 25-27, A-1121 Vienna (AT).

(72) Inventors; and
(75) Inventors/Applicants (US only): Johann PFIEFFER [AT/AT]; Siedlungsstrasse 19, A-3804 Allentsteig (AT).

(74) Representative: Ferdinand GIBLER; Dorotheergasse 7, A-1010 Vienna (AT).

(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO Patent (KE, LS, MW, SD, SZ, UG), Eurasian Patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European Patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI Patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published
With the International Search Report.
Before expiry of the period provided for amending the claims. Further publication will be made if such amendments are received.

As printed

(54) Title: METHOD OF BI-DIRECTIONAL DATA TRANSMISSION OVER A TWO-WIRE LINE

(54) Bezeichnung: VERFAHREN ZUR BIDIREKTIONALEN DATENÜBERTRAGUNG ÜBER EINE ZWEIDRAHTLEITUNG



(57) Abstract

Proposed is a method of bi-directional data transmission over a two-wire line. Digital data destined for transmission or reception, e.g. using discrete multitone modulation (DMT), are modulated or demodulated as appropriate and separated by time-division multiplexing. The appropriate multiplex time frame is subdivided into a predetermined number N of time slots and a number K of those time slots is assigned exclusively to one direction, e.g. transmission, the remaining time slots (= N-K in number) being assigned exclusively to the other direction (e.g. reception).

(57) Zusammenfassung

Verfahren zur bidirektionalen Datenubertragung über eine Zweidrahtleitung, wobei digitale Daten zum Senden oder Empfangen, z.B mittels diskreter Mehrtonmodulation (DMT), moduliert bzw. demoduliert und die zu sendenden und zu empfangenden Daten durch Zeitmultiplexbetrieb getrennt werden, wobei der zugehorige Multiplex-Zeitrahmen in eine vorbestimmbare Anzahl N von Zeitschlitzen unterteilt wird, und davon eine Anzahl K von Zeitschlitzen ausschließlich einer Übertragungsrichtung, z.B. Senden, und die restliche Anzahl (N-K) von Zeitschlitzen ausschließlich der anderen Übertragungsrichtung, z.B. Empfangen, zugeordnet wird.

Patent
Attorney's Docket No. 032287-001

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of	)	
	)	
Johann PFIEFFER	)	Group Art Unit: Unassigned
	)	
Application No.: Unassigned	)	Examiner: Unassigned
	)	
Filed: December 29, 1997	)	
	)	
For: METHOD OF BI-DIRECTIONAL DATA TRANSMISSION OVER A TWO-WIRE LINE	)	

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to examination, please amend the above-identified application as follows:

IN THE CLAIMS

Please amend claims 3, 4, 6, and 7 as follows:

Claim 3, line 1, delete "or 2".

Claim 4, line 1, delete "2 or 3,".

Claim 6, line 1, delete "claims 1 to 5" and insert therefor --claim 1--.

Claim 7, line 1, delete "claims 1 to 6" and insert therefor --claim 1--.

REMARKS

The above amendments to the claims have been made in order to eliminate multiple dependencies. Favorable action on the merits is respectfully requested.

Respectfully submitted,

BURNS, DOANE, SWECKER & MATHIS, L.L.P.

By: _____
Steven M. du Bois
Registration No. 35,023

P.O. Box 1404
Alexandria, Virginia 22313-1404
(703) 836-6620

Date: December 29, 1997

Method for bidirectional data transmission via a two-wire line

The invention relates to a method for bidirectional data transmission via a two-wire line, digital data being modulated or demodulated for transmission or reception, for example by means of discrete multitone modulation (DMT), and the data to be transmitted and the data to be received being separated, for example by frequency division multiplex operation (FDM) or echo cancelling (EC).

In order to eliminate interfering influences of data to be communicated, known methods of this type carry out separation of the e.g. DMT-modulated data in frequency division multiplex operation (FDM), different frequency ranges being defined for the two transmission directions. Another possible separation option consists in the application of the echo cancelling method (EC), in which, by using adaptive filters, the influence of the transmission section on the receiver is suppressed by adaptive filters. Other separation methods have not been used to date in this connection in the prior art.

During transmission, the FDM method generates a lower and an upper frequency band corresponding to the two transmission directions. However, since the cable attenuation is dependent on frequency, major difficulties arise in obtaining the same transmission quality for both transmission channels; in the majority of cases, the transmission quality is better in one direction than in the other. In general, however, it is desirable to be able to offer quality that is as far as possible identical for both channels. Furthermore, in FDM the variation of the transmission capacity is associated with considerable effort, since it requires matching of the bandpass filters used in each case, so that the channel bandwidth can be correspondingly increased or reduced.

The echo cancelling method that is disclosed, furthermore, in the prior art also has disadvantages, although of a different nature. Thus, near-end crosstalk is a major technical problem in this method, since the signal distance between transmitted and received signal is very large. It is therefore necessary to satisfy very high requirements made of the A/D converters provided in the transmission and reception sections, since transmitted and received signals occur simultaneously and they must be appropriately well separated. The high level differences of the transmitted and received signals require a correspondingly high resolution of the A/D converters, which, in turn, results in higher product costs.

The implementation of these known separation methods FDM and echo cancelling also requires a relatively high computer power, which greatly increase [sic] the costs for the data transmission. Particularly when being employed in cases where, such as in the case of ADSL (Asymmetric Digital Subscriber Line), for instance, high data rates are to be communicated in one transmission direction ("downstream") from a central data station to a subscriber located as part of the peripheral equipment and comparatively low data rates are to be communicated in the other transmission direction ("upstream"), the complexity created in these known data transmission methods is subject to poor utilization.

The aim of the invention is to specify a method which is distinguished by a low degree of complexity with regard to hardware use or computer power, so that it can be implemented in a simple and cost-effective manner.

Furthermore, the aim of the invention is to provide a method which enables transmissions which proceed to a great extent only in one of the two transmission directions to be carried out at a high transmission rate.

A further object of the invention is to achieve a very good transmission quality with relatively little technical outlay, the intention being that a change in the transmission capacity will be possible in a simple and cost-effective manner.

According to the invention, this is achieved by virtue of the fact that the data to be transmitted and the data to be received are separated by time division multiplex operation (TDM), the associated multiplex time frame being subdivided into a predeterminable number N of time slots, and of these a number K of time slots being assigned exclusively to one transmission direction, for example transmit, and the remaining number (N-K) of time slots being assigned exclusively to the other transmission direction, for example receive.

Since either only transmitter functions or only receiver functions are active in the method according to the invention, less processor power than in conventional methods is required, since the latter have to manage a very high internal data traffic. As a result, it is possible for a transmission which is carried out by the method according to the invention to be implemented in a very cost-effective manner.

Furthermore, the method according to the invention affords the advantage of an identical transmission quality in both transmission directions, since transmission and reception take place with the same line attenuation in TDM. As a result, both transmission directions can be implemented with the least possible quality reduction in the same frequency range. A further advantage of the method according to the invention is the very simple changing of the transmission capacity, which is enabled by corresponding selection of the number of time slots for the respective transmission direction.

In the event of asymmetric data transmission, it may be particularly advantageous if the vast majority of the data is transmitted in one transmission

direction and only a small remainder is transmitted in the other transmission direction. This is provided when the number N of time slots is selected to be very much greater than the number K. This condition is preferably fulfilled when N is equal to 30 and K is equal to 1.

Since the method according to the invention can be employed for data transmission via telephone lines, pulse-like interference may occur on the line as a result of the number dialling, for example, the interference effecting a transmission error which absolutely must be corrected. However, the data transmission does not have to be carried out via telephone lines; within the scope of the invention, the data transmission can take place via any two-wire line suitable for this purpose. Equally, extremely varied electromagnetic interference, even such that is external to the system, may influence the data transmission.

The known ARQ (Automatic Repeat Request) method is usually employed for the purpose of error correction in such a way that the data transmission remains free from errors even in the event of arbitrary interference on the line, in which case, however, the data throughput may decrease considerably since an erroneously transmitted data packet is repeated until it is received without any errors.

In a further design of the invention, therefore, it may be provided that a predeterminable number of time slots for ARQ (Automatic Repeat Request) transmission repeats are provided on average over time in the multiplex time frame of the data transmission.

Consequently, transmission overcapacity is constantly available in this embodiment. If a data block is received with errors, the receiver requests a repeat only as often as is possible within the scope of the overcapacity which is available on average over time, thereby enabling the nominal data throughput to be kept constant in a manner such that it is unaffected by the transmission repeats. A signal containing relatively high redundancy is communicated in the event of error-

free transmission. The duration of the time interval over which the time averaging takes place is essentially limited by the storage capacity of the ARQ buffer used.

According to another variant of the invention, it may be provided that in the event of erroneous transmission, the data are retransmitted after having been modified, for example by means of a computing algorithm.

This makes it possible to correct the error which occurs during transmission and is caused by the clipping of part of the amplitude in the event of transmission overmodulation.

In a particularly preferred manner, it may be provided in this case that the data are modified by logic inversion.

This inversion operation represents an algorithm which can be calculated very simply and can be realized without a high degree of complexity.

Furthermore, it may be provided that the switching frequency of an interference source, for example a power supply unit, is synchronized with one of the carrier frequencies of the discrete multitone modulation.

As a result, the DMT method, which is sensitive to frequency-selective interference, can be protected against known interference sources. When the switching frequency of the interference source is synchronized with one of the carrier frequencies of the DMT modulation, the interference acts only on this carrier frequency and multiples thereof, with the result that they can be compensated for by an adaptive algorithm.

Crosstalk, which, by its nature, has an interfering effect on the transmission, is usually produced when a plurality of two-wire lines, on each of which data are transmitted, are routed next to one another.

According to another embodiment of the method according to the invention, in which data are transmitted via two or more two-wire lines which are routed

at least partially at crosstalk distance, it may be provided that the time division multiplex operation (TDM) is carried out synchronously on all of the two-wire lines, with the result that either transmission or reception is performed simultaneously on all of the two-wire lines.

As a result, either transmission or reception is always performed at the same time, thereby making it possible to prevent the individual receivers from being influenced in an interfering manner by transmitters that are not directly connected.

The invention is explained in more detail below using an exemplary embodiment which is illustrated in the drawings.

In the figures:

Figure 1 shows a block diagram for the implementation of one embodiment of the method according to the invention, and

Figure 2 shows a diagrammatic illustration of a time frame according to the invention.

Bidirectional data transmission of digital data in accordance with the block diagram illustrated in Figure 1 is carried out in that, in the event of transmission, the digital data coming from a data source 1, 4 are converted into an analog transmission signal in the transmission section 50 and are transmitted via a line transformer 13 of a two-wire line 100 to a subscriber located at the end of this line 100. By contrast, a signal arriving on the two-wire line 100 is passed as received signal via the line transformer 13 to the input of a reception section 51, where it is converted into digital data. Since transmission and reception are never performed simultaneously in the method according to the invention, the line transformer 13 can be used instead of a hybrid that is otherwise customary, as a result of which the often problematic matching of the hybrid to the line impedance is obviated from the outset. Interfering crosstalk which is caused by a hybrid and as a result of which signal

residues pass from the transmitter to the receiver of the same subscriber end is consequently precluded as an interference source for this method.

In the exemplary embodiment shown in Figure 1, the transmission and reception sections 50, 51 both of a central data station C (CENTRAL) and of a peripheral data station R (REMOTE) are illustrated in a single block diagram, which should be understood such that the central data station C is connected to the data station R via the transformer 13, the two-wire line 100 and a further transformer 13. Those functional units which are associated only with the data station C or R are identified by "ATU-C only" or "ATU-R only".

Without restricting the general applicability of the method according to the invention, a home video system will be described as an exemplary embodiment of asymmetric data transmission, in which system the video information of different videos are stored as data in compressed form in a mainframe in the central data station C and can be called up via a peripheral data station R. The control information is exchanged between the data stations C and R via a bidirectional control channel, a data rate of 64 kbit/s being stipulated. This control information may refer to various commands to be issued by the subscriber, such as, for instance, PLAY, REWIND or the like, as are known by a video recorder, as well as internal control commands, and is comparatively modest in terms of its quantity compared with the broadband information which is sent from the central data station C and essentially comprises the video information which is transmitted at a data transmission rate of 2.048 Mbit/s only in one direction from C to R.

However, the data rates cited may alternatively be selected such that they are completely different, for example a great deal higher, for the method according to the invention, in which case even a data rate of about 50 Mbit/s to 150 Mbit/s can be made available for the broadband information to be communicated only in

one direction. The transmitted information can constitute every type of voice, image or data information. Equally, a different rate can be implemented for the bidirectional control channel, which, however, can fulfil not only control functions but all of the possible data transmission functions.

At the input part of the transmission section 50, two different data inputs are constructed for the data station C and only one data input for the data station R. The data stream from the data source 1 passes to the first input, which is identical for C and R, the data source transmitting e.g. essentially control commands which pass via a downstream scrambler 2 into a transmission buffer 3 downstream of the latter, the data coming from the data source 1 being converted according to a predeterminable algorithm in the scrambler 2. This prevents a relatively lengthy, constant logic state and achieves balanced, random distribution of the binary states. Afterwards, the scrambled signals are buffer-stored in the transmission buffer 3. In the data station R, the data issuing from the transmission buffer 3 are multiplexed by means of a device MUX with other data, which are generated in the ARQ buffer 24 and contain repeat instructions.

The data stream from the data source 4, which generates the broadband information, reaches the second input of the transmission section 50, which is designed only for the data station C, the data stream reaching the second input of the transmission section 50 via a downstream scrambler 5 and via an ARQ (Automatic Request) buffer 6, which contains a CRC generator by means of which error correction coding is carried out. The data converted in the scrambler 5 are buffer-stored in the ARQ buffer 6 and repeated in the event of erroneous transmission. A special ARQ transmission technique according to the invention will be described below.

The data arriving serially via the inputs of the transmission section 50 are combined in a predeter-

minable length in the encoder 7 in order to reduce the data rate and, using an encoding table, are assigned to a corresponding symbol for the purpose of further processing. Furthermore, this encoded signal is modulated in the downstream DMT (Discrete Multi Tone) modulator 8 according to this known method and is passed via a high-pass filter 9, which essentially suppresses the voice frequency band in order to avoid interfering influences. The digital output signal of this high-pass filter 9 is converted into an analog signal by means of a digital-to-analog converter 10, which analog signal passes via a bandpass filter 11 and then via an amplifier 12 to the transformer 13. On the one hand, the bandpass filter 11 again performs the function of the high-pass filter 11 [sic] and, on the other hand, it clips the high-frequency voltage spikes caused by the analog-to-digital [sic] converter 10. The frequency of the analog-to-digital [sic] conversion is selected to satisfy the sampling theorem such that sampling by the analog-to-digital [sic] converter 10 is effected at least twice for the highest frequencies that occur.

The transmission section 50 and the reception section 51 are controlled by a TDM (Time Division Multiplex) unit 30, with the result that, according to the invention, the data to be transmitted and the data to be received are separated by time division multiplex operation, the associated multiplex time frame being subdivided into a predeterminable number N of time slots, and of these a number K of time slots of the time frame being assigned exclusively to one transmission direction, for example transmit, whereas the remaining number N-K of time slots being assigned exclusively to the other transmission direction, for example receive. For this purpose, the TDM unit controls the transmission section 50 and the reception section 51 by activating them at the given time. In this case, the transmission section 50 and the reception section 51 are never in operation at the same time, as a result of which the processor power required

for the control can be designed to be correspondingly low. Since influencing of the receiver by its own transmitter is also precluded as a result, only a low resolution is necessary for the analog-to-digital converter 16 of the receiver section. This advantage is highly cost-effective on account of the direct proportionality of resolution and price in the case of analog-to-digital converters.

The method according to the invention has the advantage of a relatively low bandwidth requirement and a very low degree of complexity, which is reflected in the hardware and in the requisite computer power. In conventional methods for separating transmission and reception, a considerable part of the computer power is lost on internal communication, whereas in the method according to the invention, this auxiliary computer capacity can be kept very low.

The limit of the method according to the invention is where the proportion of transmission and reception approaches the 50% limit, since other methods such as echo cancelling or the like can then be implemented with the same or less complexity.

Figure 2 illustrates the time frame subdivided into time slots which is of the kind used in the method according to the invention. The two transmission directions are identified by the expressions "upstream" and "downstream". In this example, the total time frame is 20.625 ms long and is subdivided into various slots of 625 µs, the majority of the data being transmitted in the downstream direction. This division is particularly advantageous when a bidirectional channel having a low data rate and a unidirectional channel having a high data rate are required in one transmission direction. In the exemplary embodiment illustrated, control commands are transmitted via the bidirectional channel by the time slots designated by CONTROL in the downstream and upstream directions and video information is transmitted via the unidirectional channel by the 30 downstream time slots designated by VIDEO together with

one auxiliary slot on average over time. This type of transmission can be effected for any desired information items.

The distribution of the transmission and/or reception capacities can be adapted to the respective conditions by selection of the number of upstream and/or downstream time slots. In the event of changes in the capacity utilization, this ratio can be matched automatically in accordance with the current requirement. The defined transmission and reception times have the advantage over frequency division multiplex transmission that data to be received and data to be transmitted do not have to be processed simultaneously, as a result of which the computer power or the hardware outlay can be designed to be correspondingly low. One encoded and DMT-modulated data unit is transmitted in each DMT slot.

For ARQ transmission repeats, a predeterminable number of time slots for ARQ transmission repeats are provided on average over time in the multiplex time frame of the data transmission according to one embodiment according to the invention. For this purpose, when the data are transmitted, they are continually written to the ARQ transmission buffer 6 and forwarded again from the latter to the encoder 7. In this case, the data leaving the buffer 6 are transmitted more rapidly than said buffer is filled. The last data block is in each case entered anew into the resulting gap, said data block, however, being identified as a repeated block at the receiver end and being automatically eliminated. Consequently, in the event of error-free transmission, transmission is constantly performed with overcapacity, without the transmitted information content being greater.

As soon as a transmission error occurs, the receiver in the peripheral data station R detects the error by means of its CRC error detection in the ARQ unit 24 and then forwards the command for data repetition via the multiplexer of the transmission buffer 3,

which command is then transmitted as control information via the bidirectional channel. In the central data station C, this information is demultiplexed in the receiver buffer 27 after passing through the receiver section 51, and a control command to repeat the erroneous transmission is passed to the ARQ buffer 6.

In this exemplary embodiment, only one auxiliary slot is available, on average over time, for this purpose, which corresponds to an overcapacity of 3.33%. The duration and number of the auxiliary slots are not subject to any restriction in this connection and can be adapted to the respective conditions as desired within the bands of what is technically feasible.

After an erroneous transmission, the repeat transmission is then carried out in the subsequent time frame, which repeat transmission may extend over a plurality of successive time slots. Averaged over time, only one time slot per frame should be used for the repeats in this example.

The time interval over which the time average is calculated is defined by the size of the ARQ buffer store. As soon as the latter is filled to capacity with information, no further repeats can be carried out and the erroneous data block must be output as transparent.

In contrast to a conventional ARQ method, the time interval which is defined for the data repeats is fixed on average over time. As a result, it is not possible for the situation to arise where, on account of a relatively lengthy interference, the transmission is repeated until it is free from errors and, as a result, the transmission time is greatly increased. The known ARQ method causes the data transmission to be repeated even in the event of arbitrary interference until it is received without any errors, as a result of which, however, the data throughput decreases to a very great extent. In contrast, the fixed overcapacity lying between 2 and 10%, but preferably between 3 and 5%, in the method according to the invention causes the trans-

mission to be repeated only as often as is possible within the scope of the overcapacity, in order to maintain the nominal data throughput. If one of a plurality of successive incorrect data blocks can no longer be repeated and received correctly, it is output as transparent.

In the case of a signal which is modulated by discrete multitone modulation (DMT), the ratio of peak value to average value is very large, with the result that clipping of the signal peak represents a frequent error source. In order to correct this error in a simple manner, after erroneous data transmission, the digital bit train can be modified during the repeat operation in the transmitter, for example by a computing algorithm, and then retransmitted. In the receiver, the computing algorithm used is correspondingly applied inversely and the data are recovered. As a result, this transmission error can be eliminated very effectively. In particular, transmission of the erroneous data in inverted form can be implemented in a simple manner in terms of circuitry or computation.

A further interference source in the DMT method results from the switching frequency of the voltage supply used, for example of the power supply unit, since this switching frequency lies in the transmission range and, consequently, manifests its effect as frequency-selective interference. Added to this is the dependence of this interference on other influencing variables, for instance the load currently present on the power supply unit. This type of interference can be reduced by synchronizing the switching frequency of the power supply unit with one of the carrier frequencies of the DMT modulation. As a result, this interference acts only on this carrier frequency and its multiples, with the result that they can be compensated for very easily by an adaptive algorithm.

Figure 1 furthermore illustrates the reception section 51 corresponding to the transmission section 50. The signals arriving from the other subscriber end

via the two-wire line 100 and the transformer 13 are passed via a bandpass filter 14 and via an AGC (Automatic Gain Control) unit, which generates a signal of approximately constant amplitude irrespective of the instantaneous signal conditions on the line, to the input of an analog-to-digital converter 16 which is associated with the reception section 51 and whose output is connected to a high-pass filter 17. The signal present at the input of the high-pass filter 17 is fed back as manipulated variable to the AGC unit 15 via an AGC control circuit 18.

The high-pass filter 17 is followed by demodulation of the signal, from which, only in the peripheral data station R, the concomitantly transmitted pilot tone is fed to a pilot AGC unit 20, from which a reference signal for the clock generation unit 31 of the peripheral data station R is obtained in the clock recovery unit 31. This clock generation unit 31 generates the time base for the TDM unit 30 and for the system clock. The data station C does not require a clock recovery unit since an independent time base is provided there.

The linear distortion effected by the transmission path is eliminated in an equalizer 22 which follows the DMT demodulator 19 and has an update function. Afterwards, decoding in accordance with a decoding table takes place in a decoder 23, whereupon a serial bit stream is again present at the output of the decoder 23, which bit stream is passed via two outputs. The first output, which is constructed identically for data station C and R, comprises a reception buffer 27 for control information, a downstream descrambler 28, in which the data are re-established in their correct order, and the data sink 29, which receives the transmitted control data. The second output of the reception section 51, which is provided only for the data station R, is connected to an ARQ buffer 24, which buffer-stores and verifies the transmitted broadband information from the data station C and, if required, passes

the command for renewed transmission of the erroneously transmitted data via a control unit integrated in the ARQ buffer 24 to the multiplex input of the transmission buffer 3, which command is transmitted back to the data station C. Connected to the output of the ARQ buffer 24 is a descrambler 25 and, following the latter, a data sink 26 for accepting the broadband information.

If data are transmitted via two or more two-wire lines which are routed at least partially at crosstalk distance, it can happen that crosstalk occurs as a result of the mutual inductive influence of the two-wire lines. This undesirable interference may occur particularly in a central data station in which a large number of outgoing two-wire lines are routed next to one another.

In one embodiment of the method according to the invention, this type of interference is avoided by carrying out the time division multiplex operation synchronously on all of the two-wire lines. This means that either transmission or reception is performed simultaneously via all of the two-wire lines, with the result that influencing is not possible.

Patent Claims

1. A method for bidirectional data transmission via a two-wire line, digital data being modulated or demodulated for transmission or reception, for example by means of discrete multitone modulation (DMT), and the data to be transmitted and the data to be received being separated, for example by frequency division multiplex operation (FDM) or echo cancelling (EC), **wherein** the data to be transmitted and the data to be received are separated by time division multiplex operation (TDM), the associated multiplex time frame being subdivided into a predeterminable number N of time slots, and of these a number K of time slots being assigned exclusively to one transmission direction, for example transmit, and the remaining number (N-K) of time slots being assigned exclusively to the other transmission direction, for example receive.

2. The method as claimed in claim 1, **wherein** N is equal to 30 and K is equal to 1.

3. The method as claimed in claim 1 or 2, **wherein** a predeterminable number of time slots for ARQ (Automatic Repeat Request) transmission repeats are provided on average over time in the multiplex time frame of the data transmission.

4. The method as claimed in claim 1, 2 or 3, **wherein** in the event of erroneous transmission, the data are retransmitted after having been modified, for example by means of a computing algorithm.

5. The method as claimed in claim 4, **wherein** the data are modified by logic inversion.

6. The method as claimed in claims 1 to 5, **wherein** the switching frequency of an interference source, for example a power supply unit, is synchronized with one of the carrier frequencies of the discrete multitone modulation.

7. The method as claimed in claims 1 to 6, data being transmitted via two or more two-wire lines which are routed at least partially at crosstalk distance, **wherein** the time division multiplex operation (TDM) is carried out synchronously on all of the two-wire lines, with the result that either transmission or reception is performed simultaneously on all of the two-wire lines.


TRANSMITTER FUNCTIONS
RECEIVER FUNCTIONS
TRANSMITTER ACTIVATION
RECEIVER ACTIVATION
PILOT TONE
ATU-C
ATU-R
V.24
G703
SCR
DSCR
LCC TRM BUFFER
ARQ BUFFER CRC GEN.
BYTE/SYMB ENCODER
DMT MODUL.
HP
D/A
BP
TDM MANAGER
CLOCK GENERATION
VCXO
BLOCK SYNC
RECEIVE CLOCK
SYSTEM CLOCK
SAMPLE CLOCKS
EXT TDM SYNC
ARQ BUFFER CRC VERIFY ARQ MANAGER
LCC REC BUFFER
DECODER SYMB/BYTE
EQUALIZER & UPDATE
DMT DE-MODULAT.
PILOT AGC
CLOCK REC.
LEVEL DETECT
AGC
AGC CONTROL
MUX
DEMUX
50
51
100

FIG. 1


downstream
upstream
CONTROL
VIDEO
CONTROL
0
29
30
625 μs
625 μs
DMT
block
20.625 ms

FIG. 2

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY (Includes Reference to Provisional and PCT International Applications)	ATTORNEY'S DOCKET NUMBER 032287-001

As a below named inventor, I hereby declare that:
My residence, post office address and citizenship are as stated below next to my name;
I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

METHOD OF BI-DIRECTIONAL DATA TRANSMISSION OVER A TWO-WIRE LINE

the specification of which (check only one item below):

☐ is attached hereto.

☒ was filed as United States application

Number 08/981,519

on December 29, 1997

and was amended

on December 29, 1997 (if applicable).

☐ was filed as PCT international application

Number _____

on _____

and was amended under PCT Article 19

on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the Office all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, §1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, §119 (a)-(e) of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. §119:

COUNTRY (if PCT, indicate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. §119
Austria	A 1087/95	26 June 1995	X Yes __ No
			__ Yes __ No
			__ Yes __ No
			__ Yes __ No
			__ Yes __ No

I hereby claim the benefit under Title 35, United States Code § 119(e) of any United States provisional application(s) listed below.

_____ _____
(Application Number) (Filing Date)

_____ _____
(Application Number) (Filing Date)

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY (CONTINUED) (Includes Reference to Provisional and PCT International Applications)	ATTORNEY'S DOCKET NO. 032287-001

I hereby claim the benefit under Title 35, United States Code, §120 of any United States applications(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose to the Office all information known to me to be material to the patentability as defined in Title 37, Code of Federal Regulations §1.56, which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120:

U.S. APPLICATIONS		STATUS *(check one)*		
U.S. APPLICATION NUMBER	U.S. FILING DATE	PATENTED	PENDING	ABANDONED

PCT APPLICATIONS DESIGNATING THE U.S.

PCT APPLICATION NO.	PCT FILING DATE	U.S. APPLICATION NUMBERS ASSIGNED (if any)			
PCT/AT96/00112	21 June 1996	08/981,519		X	

I hereby appoint the following attorneys and agent(s) to prosecute said application and to transact all business in the Patent and Trademark Office connected therewith and to file, prosecute and to transact all business in connection with international applications directed to said invention:

William L. Mathis	17,337	Robert G. Mukai	28,531	Bruce J. Boggs, Jr.	32,344
Peter H. Smolka	15,913	George A. Hovanec, Jr.	28,223	William H. Benz	25,952
Robert S. Swecker	19,885	James A. LaBarre	28,632	Peter K. Skiff	31,917
Platon N. Mandros	22,124	E. Joseph Gess	28,510	Richard J. McGrath	29,195
Benton S. Duffett, Jr.	22,030	R. Danny Huntington	27,903	Matthew L. Schneider	32,814
Joseph R. Magnone	24,239	Eric H. Weisblatt	30,505	Michael G. Savage	32,596
Norman H. Stepno	22,716	James W. Peterson	26,057	Gerald F. Swiss	30,113
Ronald L. Grudziecki	24,970	Teresa Stanek Rea	30,427	Michael J. Ure	33,089
Frederick G. Michaud, Jr.	26,003	Robert E. Krebs	25,885	Charles F. Wieland III	33,096
Alan E. Kopecki	25,813	Robert M. Schulman	31,196	Bruce T. Wieder	33,815
Regis E. Slutter	26,999	William C. Rowland	30,888	Todd R. Walters	34,040
Samuel C. Miller, III	27,360	T. Gene Dillahunty	25,423		
Ralph L. Freeland, Jr.	16,110	Patrick C. Keane	32,858		

and: Steven M. du Bois, Registration No. 35,023

Address all correspondence to: Ronald L. Grudziecki
BURNS, DOANE, SWECKER & MATHIS, L.L.P.
P.O. Box 1404
Alexandria, Virginia 22313-1404

Address all telephone calls to: Steven M. du Bois at (703) 836-6620.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY (CONTINUED) (Includes Reference to Provisional and PCT International Applications)	ATTORNEY'S DOCKET NO. 032287-001

FULL NAME OF SOLE OR FIRST INVENTOR Johann PFEIFFER	SIGNATURE	DATE 98-03-10
RESIDENCE Allentsteig, AUSTRIA ATX		CITIZENSHIP Austria
POST OFFICE ADDRESS Siedlungsstrasse 19, A-3804 Allentsteig, AUSTRIA		
FULL NAME OF SECOND JOINT INVENTOR, IF ANY	SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF THIRD JOINT INVENTOR, IF ANY	SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF FOURTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF FIFTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF SIXTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF SEVENTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF EIGHTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		
FULL NAME OF NINTH JOINT INVENTOR, IF ANY	SIGNATURE	DATE
RESIDENCE		CITIZENSHIP
POST OFFICE ADDRESS		